

AC Surge Protector SPD I2R Module 240 Vac SASD 10 kA

1000-851 I2R 240V 10KA SASD Module



Features

- 100% SASD Protection
- SASD and MOV Protection Options
- Visual Suppression Status Indicator
- Dry Contact Remote Annunciation Wire Leads
- Replaceable Suppression Modules
- DIN-Rail Mount

Applications

- Electrical Panelboards
- Industrial Automation
- Communications Base Stations
- IT & Data Centers
- Switchgear
- Motor Control Centers
- Automatic Transfer Switches
- Wastewater Treatment
- Oil & Gas
- LED Lighting
- Schools
- Hospitals

Description

AC surge protector (also known as SPD or lightning protector) 1000-851 from Transtector is a module style SPD that utilizes state of the art SASD technology to protect critical equipment that operates on a 240 Vac electrical service. This surge protector provides effective protection against electrical transient surges that are generated both by external lightning events and by internal switching events and supports long-term system reliability by safely shunting high amounts of transient energy while maintaining a very low clamping voltage. Transtector AC surge protectors are available in stock with same day shipping.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Service Voltages	240			Vac
Maximum Continuous Operating Voltage (MCOV)			300	Vac
L - N				Vac

Surge Protection Specification

Description	Minimum	Typical	Maximum	Units
Surge Protection Technology		SASD		
Protection Modes		L-N		
8/20 μ s Surge Current			10	kA
Nominal Discharge Current Rating (In)	10			kA
Response Time			5	ns

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:
[AC Surge Protector SPD I2R Module 240 Vac SASD 10 kA 1000-851](#)

AC Surge Protector SPD I2R Module 240 Vac SASD 10 kA

1000-851 I2R 240V 10KA SASD Module



Mechanical Specifications

Size

Height	2.62 in	[66.55 mm]
Width	1.8 in	[45.72 mm]
Depth	0.98 in	[24.89 mm]
Weight	1 lbs	[453.59 g]
Housing Material and Plating	Lexan 940-701 Black	

Environmental Specifications

Temperature Range (Operational)	-20 to +65 deg C
Humidity	90% non-condensing

Installation

Mount Type	Plug-In
------------	---------

Transtector Systems specializes in protection of highly sensitive, low voltage equipment through its patented, non-degrading silicon diode technology and custom filters. Our power quality expertise translates into a diverse product offering including AC, DC, and signal applications as well as integrated cabinets, power distribution panels and EMP hardened devices.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [AC Surge Protector SPD I2R Module 240 Vac SASD 10 kA 1000-851](#)

URL: <https://www.transtector.com/ac-surge-protector-spd-i2r-module-240-1000-851-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Transtector reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Transtector does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Transtector does not assume any liability arising out of the use of any part or documentation.

1000-851 CAD Drawing

REVISIONS		DATE	APPROVED
REV.	DESCRIPTION		
A	INITIAL RELEASE	1/19/19	DWR



TRANSTECTOR

THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF TRANSTECTOR CORPORATION. ALL RIGHTS RESERVED.

TRANSTECTOR

10701 AIRPORT ROAD, HAYDEN, ID 83835
PHONE: 1-208-635-6400 | 1-800-882-9110
FAX: 1-208-955-2041
www.transector.com | e-mail: sales@transector.com


SCALESHEET 1 OF 1
1:1 REV A


UNLESS OTHERWISE SPECIFIED
LEADING DIMENSIONS ARE INCHES
DIMENSIONS IN [] ARE MILLIMETERS


TOLERANCES:


$X \pm .2$	[5.08]	FRACTIONS
$XX \pm .01$	[.25]	$\pm 1/32$
$XXX \pm .005$	[.13]	ANGLES $\pm 1^\circ$

ALL DIMENSIONS SHOWN
ARE FOR REFERENCE ONLY.
THIRD-ANGLE PROJECTION










POWER STATUS LED



SUPPRESSION STATUS LED

