

Data Surge Protector SPD ALPU Outdoor 10/100 Base-T Ethernet/24V PoE Shielded RJ45 SASD, Metal Enclosure

1101-1144 ALPU-POE-36-M



Features

- Models for all Common Ethernet/PoE Protocols
- Shielded RJ-45 or Punch Down Block Wiring

Applications

- 10/100 Base-T Ethernet/24V PoE Networks
- · Telecommunications Base Stations
- WISP/ISP
- IT & Data Centers

- Pole or Wall Mount
- Point-to-Point Links
- · Control Lines and Sense Loops
- Oil & Gas

Description

Data surge protector (also known as SPD or lightning protector) 1101-1144 from Transtector is an outdoor style SPD that utilizes state of the art SASD technology to protect critical equipment in 10/100 Base-T Ethernet/24V PoE protocol data networks while remaining transparent to data throughput. This surge protector provides effective protection against electrical transient surges that are generated both by external lightning events and by internal switching events and supports long-term system reliability by absorbing high amounts of transient energy while maintaining a very low clamping voltage. Transfector Data Signal surge protectors are available in stock with same day shipping.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Connectors		Shielded RJ45		
Compatible Cables	Cat5/5e UTP/STP, Cat6/6A STP			
Data Protocols	1	0/100 Base-T Ethernet/24V PoE		
Data Rate			100	Mb/s
Characteristic Impedance			100	Ohms
Power over Ethernet Protocols		PoE		
Vdc Rating (Data)		24	36	Vdc
PoE Power			24	W
PoE Current Per Pin			1	А

Surge Protection Specification

Description	Minimum	Typical	Maximum	Units
Surge Protection Technology		SASD		

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Data Surge Protector SPD ALPU Outdoor 10/100 Base-T Ethernet/24V PoE Shielded RJ45 SASD, Metal Enclosure 1101-1144



Data Surge Protector SPD ALPU Outdoor 10/100 Base-T Ethernet/24V PoE Shielded RJ45 SASD, Metal Enclosure

1101-1144 ALPU-POE-36-M



Protected Pins	[1,2], [3,6], [4,5], [7,8]		
Protection Modes	L-G, L-L		
0/1000µs Surge Current			
L-G		100	Α
/pl 10/1000µs			
L-G	40 @ 100A		Vpk
Response Time		5	ns

Mechanical Specifications

Size

Height	7.15 in	[181.61 mm]
Width	5.69 in	[144.53 mm]
Depth	1.65 in	[41.91 mm]
Weight	0.8 lbs	[362.87 g]

Environmental Specifications

Operating Temperature -40 to +80 deg C Storage Temperature -40 to +80 deg C

Environmental Protection Rating

Mount Type

Wall

Wall

**C X 1" So

Installation Hardware #6 X 1" Self-Tapping Screw, Anchor

Grounding 1/4-20 Screw, Washer

Compliance Certifications

Certifications

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Data Surge Protector SPD ALPU Outdoor 10/100 Base-T Ethernet/24V PoE Shielded RJ45 SASD, Metal Enclosure 1101-1144



Data Surge Protector SPD ALPU Outdoor 10/100 Base-T Ethernet/24V PoE Shielded RJ45 SASD, Metal Enclosure

1101-1144 ALPU-POE-36-M



Transtector Systems specializes in protection of highly sensitive, low voltage equipment through its patented, non-degrading silicon diode technology and custom filters. Our power quality expertise translates into a diverse product offering including AC, DC, and signal applications as well as integrated cabinets, power distribution panels and EMP hardened devices.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Data Surge Protector SPD ALPU Outdoor 10/100 Base-T Ethernet/24V PoE Shielded RJ45 SASD, Metal Enclosure 1101-1144

URL: https://www.transtector.com/data-surge-protector-spd-alpu-outdoor-10-1101-1144-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Transfector reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Transfector does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Transfector does not assume any liability arising out of the use of any part or documentation.

1101-1144 CAD Drawing

