

## AC Surge Protector SPD DR DIN-Rail 240 Vac Single-Phase 20 A SASD 700 A, UL 94-V0

### 1101-347 DR 240

#### Features

- 100% SASD Protection
- Suppression Status LED
- Dry Contact Remote Annunciation Wire Leads
- Replaceable Suppression Modules
- WAGO Cage Clamp Wiring Terminals
- DIN-Rail Mount

#### Applications

- Electrical Panelboards
- Industrial Automation
- Communications Base Stations
- IT & Data Centers
- Switchgear
- Motor Control Centers
- Automatic Transfer Switches
- Wastewater Treatment
- Oil & Gas
- LED Lighting
- Schools
- Hospitals

#### Description

AC surge protector (also known as SPD or lightning protector) 1101-347 from Transtector is a UL 94-V0 DIN-Rail style SPD that utilizes state of the art SASD technology to protect critical equipment that operates on a 240 Vac Single-Phase electrical service. This surge protector provides effective protection against electrical transient surges that are generated both by external lightning events and by internal switching events and supports long-term system reliability by safely shunting high amounts of transient energy while maintaining a very low clamping voltage. Transtector AC surge protectors are available in stock with same day shipping.

#### Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Service Voltages		240		Vac
Service Type		Single-Phase		
Current Rating			20	A
Maximum Continuous Operating Voltage (MCOV)				
L - N			280	Vac

#### Surge Protection Specification

Description	Minimum	Typical	Maximum	Units
Surge Protection Technology		SASD		
Protection Modes		L-N		
8/20 $\mu$ s Surge Current			0.7	kA

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:  
[AC Surge Protector SPD DR DIN-Rail 240 Vac Single-Phase 20 A SASD 700 A, UL 94-V0 1101-347](#)

AC Surge Protector SPD DR DIN-Rail 240 Vac Single-Phase 20 A SASD 700 A, UL 94-V0

**1101-347**  
**DR 240**

Nominal Discharge Current Rating (In)	0.7	kA
V <sub>pl</sub> 8/20μs L-N	440	V <sub>pk</sub>
Response Time	5	ns

**Mechanical Specifications**

**Size**

Height	3.5 in	[88.9 mm]
Width	0.9 in	[22.86 mm]
Depth	2.9 in	[73.66 mm]
Weight	0.18 lbs	[81.65 g]
Housing Material and Plating	Plastic	UL94 V-0

**Environmental Specifications**

Temperature Range (Operational)	-40 to +85 deg C
Temperature Range (Storage)	-40 to +85 deg C
Humidity	95% non-condensing

**Installation**

Mount Type	DIN Rail
------------	----------

**Compliance Certifications**

UL Compliant	Yes
Certifications	UL 94-V0

Transtector Systems specializes in protection of highly sensitive, low voltage equipment through its patented, non-degrading silicon diode technology and custom filters. Our power quality expertise translates into a diverse product offering including AC, DC, and signal applications as well as integrated cabinets, power distribution panels and EMP hardened devices.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [AC Surge Protector SPD DR DIN-Rail 240 Vac Single-Phase 20 A SASD 700 A, UL 94-V0 1101-347](#)

URL: <https://www.transtector.com/ac-surge-protector-spd-dr-din-rail-1101-347-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Transtector reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Transtector does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Transtector does not assume any liability arising out of the use of any part or documentation.

## 1101-347 CAD Drawing

