

RMP Rack Mount PDU AC Indoor 1RU 120 Vac Single-Phase 20A NEMA L5-20 Plug Inlets 4x NEMA 5-20 Outlets Per Feed SASD Fused

1101-560
RMP 2-420A



Features

- 100% SASD Protection
- Various Configurations For Standard Power Feeds
- Suppression Status LEDs
- Replaceable Fuses
- 2x 15' Power Cords
- 1RU Rack Mount
- Mount Type 19" Rack Mount
- Surge Protection Status LEDs: GRN=Operational, RED=Fail

Applications

- Power Distribution
- Industrial Automation
- Telecommunications Base Stations
- First Responder Sites
- Emergency Management Systems
- Load Expansion

Description

Rack mount power distribution unit (also known as PDU) 1101-560 from Transtector is an AC 1RU PDU that accepts a 120 Vac 2x single-phase feed electrical service and distributes power to individual loads via 4x NEMA 5-20 outlets per feed. This rack mount unit equipped with state-of-the-art SASD surge protection that provides lightning protection for downstream equipment to support long-term system reliability. Transtector rack mount PDUs are available in stock with same day shipping.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Service Voltage			120	Vac
Frequency Range	50		60	Hz
Current Rating			20	A
Number of Outlets NEMA 5-20 Outlets		8		

Surge Protection Specification

Description	Minimum	Typical	Maximum	Units
Surge Protection Technology		SASD		
8/20 μ s Surge Current			3	kA
10/1000 μ s Surge Current			0.25	kA
Vpl 8/20 μ s L-G			275 @ 500A	Vpk

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:
[RMP Rack Mount PDU AC Indoor 1RU 120 Vac Single-Phase 20A NEMA L5-20 Plug Inlets 4x NEMA 5-20 Outlets Per Feed SASD Fused 1101-560](#)

RMP Rack Mount PDU AC Indoor 1RU 120 Vac Single-Phase 20A NEMA L5-20 Plug Inlets 4x NEMA 5-20 Outlets Per Feed SASD Fused

1101-560
RMP 2-420A

Mechanical Specifications

Size

Length	4.5 in	[114.3 mm]
Width	19 in	[482.6 mm]
Height	1.72 in	[43.69 mm]
Weight	9 lbs	[4.08 kg]
Enclosure Material and Plating	Steel, Powder Coated Black	

Installation

Mount Type	19" Rack Mount
------------	----------------

Environmental Specifications

Temperature Continuous	-30 to +65 deg C
Temperature Momentary	-40 to +80 deg C

Transtector Systems specializes in protection of highly sensitive, low voltage equipment through its patented, non-degrading silicon diode technology and custom filters. Our power quality expertise translates into a diverse product offering including AC, DC, and signal applications as well as integrated cabinets, power distribution panels and EMP hardened devices.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [RMP Rack Mount PDU AC Indoor 1RU 120 Vac Single-Phase 20A NEMA L5-20 Plug Inlets 4x NEMA 5-20 Outlets Per Feed SASD Fused 1101-560](#)

URL: <https://www.transtector.com/rmp-rack-mount-pdu-ac-indoor-1ru-1101-560-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Transtector reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Transtector does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Transtector does not assume any liability arising out of the use of any part or documentation.

RMP Rack Mount PDU AC Indoor 1RU 120 Vac Single-Phase 20A NEMA
L5-20 Plug Inlets 4x NEMA 5-20 Outlets Per Feed SASD Fused

1101-560 CAD Drawing

