

Data Surge Protector SPD DPR Indoor 10/100 Base-T Ethernet RJ45 SASD



1101-828-1DPR 10/100 BASE-TX

Features

- Purpose Designed Modules for all Common Data Protocols
- · Configurable Mixed Signal Protection

Applications

- 10/100 Base-T Ethernet Networks
- Telecommunications Base Stations
- WISP/ISP
- · IT & Data Centers

- RJ-45 Connectivity
- Mount into DPR Chassis, DIN-Rail Mount or Wall Mount
- · Point-to-Point Links
- · Control Lines and Sense Loops
- Oil & Gas

Description

Data surge protector (also known as SPD or lightning protector) 1101-828-1 from Transfector is an indoor style SPD that utilizes state of the art SASD technology to protect critical equipment in 10/100 Base-T Ethernet protocol data networks while remaining transparent to data throughput. This surge protector provides effective protection against electrical transient surges that are generated both by external lightning events and by internal switching events and supports long-term system reliability by absorbing high amounts of transient energy while maintaining a very low clamping voltage. Transfector Data Signal surge protectors are available in stock with same day shipping.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Connectors		RJ45		
Compatible Cables		Cat5/5e UTP		
Data Protocols		10/100 Base-T Ethernet		
Data Rate			100	Mb/s
Characteristic Impedance			100	Ohms
Vdc Rating (Data)		5	6	Vdc

Surge Protection Specification

Description	Minimum	Typical	Maximum	Units
Surge Protection Technology		SASD		
Protected Pins		[1,2], [3,6], [4,5], [7,8]		
Protection Modes		L-G, L-L		

10/1000µs Surge Current

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Data Surge Protector SPD DPR Indoor 10/100 Base-T Ethernet RJ45 SASD 1101-828-1



Data Surge Protector SPD DPR Indoor 10/100 Base-T Ethernet RJ45 SASD



1101-828-1DPR 10/100 BASE-TX

L-G	100	Α
pl 10/1000µs		
ol 10/1000μs L-L	50 @ 100A	Vpk
esponse Time	5	ns

Mechanical Specifications Size

Height	0.91 in	[23.11 mm]
Width	0.97 in	[24.64 mm]
Depth	3.71 in	[94.23 mm]
Weight	0.1 lbs	[45.36 g]

Environmental Specifications

Operating Temperature -40 to +75 deg C Storage Temperature -40 to +75 deg C

Mount Type Wall, DIN, Rack Installation Hardware DIN Clip, #8 Screw

Compliance Certifications

Certifications NOM

Transtector Systems specializes in protection of highly sensitive, low voltage equipment through its patented, non-degrading silicon diode technology and custom filters. Our power quality expertise translates into a diverse product offering including AC, DC, and signal applications as well as integrated cabinets, power distribution panels and EMP hardened devices.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Data Surge Protector SPD DPR Indoor 10/100 Base-T Ethernet RJ45 SASD 1101-828-1

URL: https://www.transtector.com/data-surge-protector-spd-dpr-indoor-10-1101-828-1-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Data Surge Protector SPD DPR Indoor 10/100 Base-T Ethernet RJ45 SASD 1101-828-1



Data Surge Protector SPD DPR Indoor 10/100 Base-T Ethernet RJ45 SASD

Name in the last of the last o

1101-828-1DPR 10/100 BASE-TX

make modifications to the part and/or the documentation of the part, in order to implement improvements. Transtector reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Transtector does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Transtector does not assume any liability arising out of the use of any part or documentation.

1101-828-1 CAD Drawing

