

AC Surge Protector SPD LS PLUS Panel 120/208 Vac Split-Phase MOV 200 kA, UL 1449 5th Ed. with Disconnect

B39-00-2004



LEA LS PLUS 200 120/208-3Y-D

Features

- UL1449 5th Ed. Type 1/Type 2
- High Capacity MOV Protection
- Suppression Status LEDs
- Surge Counter
- Audible Alarm
- Dry Contact Remote Annunciation Wire Leads
- Integral Disconnect Switch

Applications

- Electrical Panelboards
- Industrial Automation
- Communications Base Stations
- IT & Data Centers
- Switchgear
- Motor Control Centers
- Automatic Transfer Switches
- Wastewater Treatment
- Oil & Gas
- LED Lighting
- Schools
- Hospitals

Description

AC surge protector (also known as SPD or lightning protector) B39-00-2004 from Transtector is a UL1449 5th Ed. panel style SPD that utilizes state of the art MOV technology to protect critical equipment that operates on a 120/208 Vac split-phase electrical service. This surge protector provides effective protection against electrical transient surges that are generated both by external lightning events and by internal switching events and supports long-term system reliability by safely shunting high amounts of transient energy while maintaining a very low clamping voltage. Transtector AC surge protectors are available in stock with same day shipping.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Service Voltages		120/208		Vac
Service Type		Split-Phase		
Frequency	50		60	Hz
Maximum Continuous Operating Voltage (MCOV) L - L			276	Vac
Maximum Continuous Operating Voltage (MCOV) L - N			138	Vac
Maximum Continuous Operating Voltage (MCOV) L - G			138	Vac
Maximum Continuous Operating Voltage (MCOV) N - G			138	Vac

Surge Protection Specification

Description	Minimum	Typical	Maximum	Units
Surge Protection Technology		MOV		
Protection Modes		L-N, L-G, L-L, N-G		

AC Surge Protector SPD LS PLUS Panel 120/208 Vac Split-Phase MOV 200 kA, UL 1449 5th Ed. with Disconnect



B39-00-2004

Surge Protection Specification

Description	Minimum	Typical	Maximum	Units
8/20µs Surge Current			200	kA
Nominal Discharge Current Rating (In)		20		
VPR 8/20µs				
L - L			1,200	Vpk
VPR 8/20µs				
L - N			800	Vpk
VPR 8/20µs				
L - G			900	Vpk
VPR 8/20µs				
N - G			900	Vpk
Response Time			25	ns
SCCR (Short Circuit Current Rating)	100			kAIC

Mechanical Specifications

Size		
Height	20 in	[508 mm].
Width	16 in	[406.4 mm]
Depth	7 in	[177.8 mm]
Weight	33 lbs	[14.97 kg]
Housing Material and Plating	Steel	

Environmental Specifications

Temperature Range (Operational)	-40 to +65 deg C
Environmental Protection Rating	NEMA 3R
Humidity	95% non-condensing

Installation

Mount Type	Panel
------------	-------

Compliance Certifications

UL Compliant Certifications	Yes
	UL 1449 5th Ed.

AC Surge Protector SPD LS PLUS Panel 120/208 Vac Split-Phase MOV 200 kA, UL 1449 5th Ed. with Disconnect

B39-00-2004

Transtector Systems specializes in protection of highly sensitive, low voltage equipment through its patented, non-degrading silicon diode technology and custom filters. Our power quality expertise translates into a diverse product offering including AC, DC, and signal applications as well as integrated cabinets, power distribution panels and EMP hardened devices.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [AC Surge Protector SPD LS PLUS Panel 120/208 Vac Split-Phase MOV 200 kA, UL 1449 5th Ed. with Disconnect B39-00-2004](https://www.transtector.com/ac-surge-protector-spd-ls-plus-panel-b39-00-2004-p.aspx)

URL: <https://www.transtector.com/ac-surge-protector-spd-ls-plus-panel-b39-00-2004-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Transtector reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Transtector does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Transtector does not assume liability arising out of the use of any part or document.

B39-00-2004 CAD Drawing

AC Surge Protector SPD LS PLUS Panel 120/208 Vac Split-Phase MOV 200 kA, UL 1449 5th Ed. with Disconnect

