

DC Breaker, 1U, Blank

DCBKR1B-BLANK



Features

- Branch Breakers for DCPDU1B Rack Mount DC PDUs
- Field-Configurable
- UL489 Listed

Applications

- Telecommunications Base Stations
- Land Mobile Radio
- First Responder Sites
- Emergency Management Systems
- Industrial Automation
- Utilities

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Maximum Continuous Operating Voltage (MCOV)				
Line to Return			80	Vdc

Mechanical Specifications

Weight 0.25 lbs [113.4 g]

Monitoring and Control

Alarm Relays 0

Compliance Certifications

RoHS Compliant Yes

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:
[DC Breaker, 1U, Blank DCBKR1B-BLANK](#)

DC Breaker, 1U, Blank

DCBKR1B-BLANK

DC Circuit Breaker



Transtector Systems specializes in protection of highly sensitive, low voltage equipment through its patented, non-degrading silicon diode technology and custom filters. Our power quality expertise translates into a diverse product offering including AC, DC, and signal applications as well as integrated cabinets, power distribution panels and EMP hardened devices.

Click the following link (or enter part number in “SEARCH” on website) to obtain additional part information including price, inventory and certifications: [DC Breaker, 1U, Blank DCBKR1B-BLANK](#)

URL: <https://www.transtector.com/dc-circuit-breaker-rack-mount-pdu-dc-dcbkr1b-blank-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Transtector reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Transtector does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Transtector does not assume any liability arising out of the use of any part or documentation.

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	1/21/21	DWR



BREAKER BLANK

UNLESS OTHERWISE SPECIFIED
LEADING DIMENSIONS ARE INCHES
DIMENSIONS IN [] ARE MILLIMETERS

TOLERANCES:		
$X = \pm 2$	[5.08]	FRACTIONS
$XX = \pm 02$	[.51]	$\pm 1/32$
$XXX = \pm .005$	[.13]	ANGLES $\pm 1^\circ$
CABLE LENGTH (L) TOLERANCES:		
$L \leq 12$ [305] = +1 [25] / -0		
12 [305] < $L \leq 60$ [1524] = +2 [51] / -0		
60 [1524] < $L \leq 120$ [3048] = +4 [102] / -0		
120 [3048] < $L \leq 300$ [7620] = +6 [152] / -0		
300 [7620] < $L = +5\%$ / -4		

ALL DIMENSIONS SHOWN
ARE FOR REFERENCE ONLY.

TRANSTECTOR

THIRD-ANGLE PROJECTION



an INFINITI® brand
10701 Airport Road, Hayden, ID 83835

Phone: 1.208.635.6400 1.800.882.9110	Fax: 1.208.955.2041	Website: www.transtector.com	E-mail: sales@transtector.com
		SHEET 1 OF 1	
		SCALE 1:1	

ITEM	CAGE CODE	DRAWN BY	ITEM NO.	REV
A	30992	DPM	DCBKR1B-BLANK	A

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.