



14x12x07 Fiberglass Reinf Polyester FRP Weatherproof Outdoor IP24 NEMA 3R Enclosure. 120 VAC MNT PLT Vented Lid Gray



TEF141207-10V

Features

- · Molded Fiberglass Reinforced Polyester (FRP) industrial
- Stainless steel guick release latches with padlock hasps
- NEMA Type 3R / IP24 rated

Applications

- Remote wireless LAN WiFi equipment installations
- · Indoor and outdoor installations
- · Rapid deployment installations

- · Fully gasketed raised vented lid with filters & integral mounting
- Features aluminum mounting plate with surge protected duplex 120 VAC outlets
- Corrosive environments & hotspot
- · Protection of equipment from theft or damage

Description

The box is a rugged weatherproof enclosure that is ideal for both indoor and outdoor applications. Constructed from molded fiberglass reinforced polyester, it is well suited for high temperature or corrosive environments. The integrated mounting flange allows it to be mounted directly to any flat wall surface provided proper screws are used into secure studs. The enclosure can also be mounted to a wide diameter range of poles with one of our optional pole mounting hardware kits. The raised lid features a stainless steel continuous hinge and stainless steel quick release latches with padlock hasps. Includes fully gasketed vented lid with filters & integral mounting flange. The enclosure material is UV stabilized and comes in machine tool gray.

Mounting Plate

The modified aluminum mounting plate included with the TEF141207-10V features standard surge protected duplex 120 VAC outlets and a terminal block for easy hook up to externally provided line power. The enclosure also features holes for two N-Bulkhead lightning protectors or connectors, a grounding lug, and a cable conduit connector.

The TEF-PMT series of pole mounting kits allow the populated enclosure to be securely mounted to a variety of different size poles.

Compatible versions include TEF-PMT13, TEF-PMT16, TEF-PMT28, TEF-PMT29, TEF-PMT30 & TEF-PMT33

Mechanical Specifications

Size	
Outer Height	
Outer Width	
Outer Depth	
Inner Height	
Inner Width	
Inner Depth	
Weight	
Enclosure Material	

15.5 in [393.7 mm] 13.32 in [338.33 mm] 8.26 in [209.8 mm] 14 in [355.6 mm] [304.8 mm] 12 in 7.95 in [201.93 mm] 11.2 lbs [5.08 kg]

Fiberglass Reinforced Polyester (FRP)

Environmental Specifications

Temperature Continuous -50 to +150°C **NEMA** Rating 3R IP24 Ingress Protection (IP) Rating

Compliance Certifications

UL Listed No





14x12x07 Fiberglass Reinf Polyester FRP Weatherproof Outdoor IP24 NEMA 3R Enclosure, 120 VAC MNT PLT Vented Lid Gray



TEF141207-10V

Transtector Systems specializes in protection of highly sensitive, low voltage equipment through its patented, non-degrading silicon diode technology and custom filters. Our power quality expertise translates into a diverse product offering including AC, DC, and signal applications as well as integrated cabinets, power distribution panels and EMP hardened devices.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 14x12x07 Fiberglass Reinf Polyester FRP Weatherproof Outdoor IP24 NEMA 3R Enclosure, 120 VAC MNT PLT Vented Lid Gray TEF141207-10V

URL: https://www.transtector.com/14x12x07-fiberglass-reinf-polyester-frp-weatherproof-outdoor-tef141207-10v-p.aspx

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. Transfector reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Transfector does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Transfector does not assume liability arising out of the use of any part or document.

TEF141207-10V CAD Drawing

14x12x07 Fiberglass Reinf Polyester FRP Weatherproof Outdoor IP24 NEMA 3R Enclosure, 120 VAC MNT PLT Vented Lid Gray

