

14x12x07 Fiberglass Reinf Polyester FRP Weatherproof Outdoor IP24 NEMA 3R Enclosure, 240 VAC UNIV. Outlet MNT PLT, MECH Thermostat Fan Gray



## TEF141207-E0F

#### **Features**

- Molded Fiberglass Reinforced Polyester (FRP) industrial enclosure
- Stainless steel quick release latches with padlock hasps
- NEMA Type 3R / IP24 rated

#### **Applications**

- · Remote wireless LAN WiFi equipment installations
- · Indoor and outdoor installations
- · Hot and cold temperature environments

- Fully gasketed raised vented lid with filters & integral mounting flange
- Features aluminum mounting plate with universal duplex socket for 200-240 VAC power & thermostat controlled cooling system
- · Corrosive environments & hotspot
- · Protection of equipment from theft or damage

## **Description**

The box is a rugged weatherproof enclosure that is ideal for both indoor and outdoor applications. Constructed from molded fiberglass reinforced polyester, it is well suited for high temperature or corrosive environments. The integrated mounting flange allows it to be mounted directly to any flat wall surface provided proper screws are used into secure studs.

The enclosure can be also be mounted to a wide diameter range of poles with one of our optional pole mounting hardware kits.

The raised lid features a stainless steel continuous hinge and stainless steel quick release latches with padlock hasps. Includes fully gasketed vented lid with filters & integral mounting flange. The enclosure material is UV stabilized and comes in machine tool gray.

### Mounting Plate

The aluminum mounting plate included with the TEF141207-E0F features a duplex 120-240 VAC Universal EURO outlet and a terminal block for easy hook up to externally provided line power. The enclosure also features holes for two N-Bulkhead lightning protectors or connectors, a grounding lug, and a cable conduit connector.

## Cooling

To help ensure trouble-free operation of electronic equipment, proper operating temperatures inside an enclosure needs to be maintained. With the built-in cooling fan, internal temperatures can be better maintained. This model is ideal in Hot environments.

For cooling the TEF141207-E0F model includes a thermostat-controlled 18W fan. The high airflow, low noise fan used allows warm air to be actively pushed out while the lower vent passively pulls in outside air into the enclosure. Filters for both ports prevent foreign objects or debris from entering the enclosure. The fan turns on when the internal temperature rises to  $120^{\circ}$  F  $(49^{\circ}$  C)  $\pm 5^{\circ}$  and turns off at  $90^{\circ}$  F  $(32^{\circ}$  C)  $\pm 10^{\circ}$ .

The TEF-PMT series of pole mounting kits allow the populated enclosure to be securely mounted to a variety of different size poles.

Compatible versions include TEF-PMT13, TEF-PMT16, TEF-PMT28, TEF-PMT29, TEF-PMT30 & TEF-PMT33

### **Mechanical Specifications**

| Size               |                                       |             |
|--------------------|---------------------------------------|-------------|
| Outer Height       | 15.5 in                               | [393.7 mm]  |
| Outer Width        | 13.32 in                              | [338.33 mm] |
| Outer Depth        | 8.26 in                               | [209.8 mm]  |
| Inner Height       | 14 in                                 | [355.6 mm]  |
| Inner Width        | 12 in                                 | [304.8 mm]  |
| Inner Depth        | 7.95 in                               | [201.93 mm] |
| Weight             | 10.9 lbs                              | [4.94 kg]   |
| Enclosure Material | Fiberglass Reinforced Polyester (FRP) |             |





14x12x07 Fiberglass Reinf Polyester FRP Weatherproof Outdoor IP24 NEMA 3R Enclosure, 240 VAC UNIV. Outlet MNT PLT, MECH Thermostat Fan Gray



## TEF141207-E0F

# **Environmental Specifications**

Temperature Continuous -50 to +150°C NEMA Rating 3R Ingress Protection (IP) Rating IP24

#### **Compliance Certifications**

UL Listed No

Transtector Systems specializes in protection of highly sensitive, low voltage equipment through its patented, non-degrading silicon diode technology and custom filters. Our power quality expertise translates into a diverse product offering including AC, DC, and signal applications as well as integrated cabinets, power distribution panels and EMP hardened devices.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 14x12x07 Fiberglass Reinf Polyester FRP Weatherproof Outdoor IP24 NEMA 3R Enclosure, 240 VAC UNIV. Outlet MNT PLT, MECH Thermostat Fan Gray TEF141207-E0F

URL: https://www.transtector.com/14x12x07-fiberglass-reinf-polyester-frp-weatherproof-outdoor-tef141207-e0f-p.aspx

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. Transfector reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Transfector does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Transfector does not assume liability arising out of the use of any part or document.

# TEF141207-E0F CAD Drawing

14x12x07 Fiberglass Reinf Polyester FRP Weatherproof Outdoor IP24 NEMA 3R Enclosure, 240 VAC UNIV. Outlet MNT PLT, MECH Thermostat Fan Gray

