

DC Surge Protector SPD DC DEFENDER Outdoor Clamshell 48 Vdc,
Full-Mode, 5 kA SASD EN/IEC 60950-1, Class I/Div II, ATEX, Fused



1101-1110 DC Defender 48-5

Features

- UL 497B, Class I/Div II, ATEX
- 100% SASD Protection
- Screw Terminal Block
- Pole or Wall Mount

Applications

- Industrial Automation
- Controls & Sense Loops
- Telecommunications Base Stations
- IT & Data Centers
- Wastewater Treatment
- Rail
- Oil & Gas
- LED Lighting

Description

DC surge protector (also known as SPD or lightning protector) 1101-1110 from Transtector is a UL 497B, Class I/Div II, ATEX Clamshell style SPD that utilizes state of the art SASD technology to protect critical equipment that operates on a 48 Vdc electrical service. This surge protector provides effective protection against electrical transient surges that are generated both by external lightning events and by internal switching events and supports long-term system reliability by safely shunting high amounts of transient energy while maintaining a very low clamping voltage. Transtector DC surge protectors are available in stock with same day shipping.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Service Voltages	48			Vdc
Current Rating			15	A
Maximum Continuous Operating Voltage (MCOV)				
MCOV DC			60	Vdc

Surge Protection Specification

Description	Minimum	Typical	Maximum	Units
Surge Protection Technology		SASD		
Surge Protection Modes		DC+ to DC-, DC+ to GND, DC- to GND		
Response Time			5	ns
8/20μs Surge Current			5	kA
VPL 8/20μs L-G			97 @ 500A	Vpk

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:
[DC Surge Protector SPD DC DEFENDER Outdoor Clamshell 48 Vdc, Full-Mode, 5 kA SASD EN/IEC 60950-1, Class I/Div II, ATEX, Fused 1101-1110](#)

DC Surge Protector SPD DC DEFENDER Outdoor Clamshell 48 Vdc,
Full-Mode, 5 kA SASD EN/IEC 60950-1, Class I/Div II, ATEX, Fused



1101-1110 DC Defender 48-5

Mechanical Specifications

Size

Height	7.17 in	[182.12 mm]
Width	5.69 in	[144.53 mm]
Depth	1.65 in	[41.91 mm]
Weight	1 lbs	[453.59 g]
Housing Material and Plating	Aluminum	

Environmental Specifications

Temperature

Operating Range	-40 to +85 deg C
Storage Range	-40 to +85 deg C
Humidity	<95% non-condensing

Installation

Mount Type	Pole, Wall/Panel
Service Wiring Terminal	#14 to #10 AWG

Compliance Certifications

CE Compliant	Yes
UL Compliant	Yes
ANSI Compliant	Yes
Hazardous Locations	Yes
Certifications	UL 497B CSA ETL 60950-1 EN 60079-0 EN 60079-15 Class I Division 2 Groups A,B,C,D T4 Class I Zone 2 AEx ec IIC T4 Gc Ex ec IIC T4 Gc II 3 G Ex ec IIC T4 Gc ITS15ATEX48178X ETL14CA101699377X

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:
DC Surge Protector SPD DC DEFENDER Outdoor Clamshell 48 Vdc, Full-Mode, 5 kA SASD EN/IEC 60950-1, Class I/Div II, ATEX, Fused 1101-1110

DC Surge Protector SPD DC DEFENDER Outdoor Clamshell 48 Vdc,
Full-Mode, 5 kA SASD EN/IEC 60950-1, Class I/Div II, ATEX, Fused



1101-1110

DC Defender 48-5

Transtector Systems specializes in protection of highly sensitive, low voltage equipment through its patented, non-degrading silicon diode technology and custom filters. Our power quality expertise translates into a diverse product offering including AC, DC, and signal applications as well as integrated cabinets, power distribution panels and EMP hardened devices.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [DC Surge Protector SPD DC DEFENDER Outdoor Clamshell 48 Vdc, Full-Mode, 5 kA SASD EN/IEC 60950-1, Class I/Div II, ATEX, Fused 1101-1110](#)

URL: <https://www.transtector.com/dc-surge-protector-spd-dc-defender-outdoor-1101-1110-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Transtector reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Transtector does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Transtector does not assume any liability arising out of the use of any part or documentation.

1101-1110 CAD Drawing

