

AC Surge Protector SPD MCP Panel 120/240 Vac Split-Phase SASD, MOV 130 kA

1101-424 MCP 120TA-10M OD



Features

- SASD/MOV Protection
- Power and Suppression Status LEDs
- Dry Contact Remote Annunciation Wire Leads
- Wall Mount

Applications

- Electrical Panelboards
- Industrial Automation
- Communications Base Stations
- IT & Data Centers
- Switchgear
- Motor Control Centers
- Automatic Transfer Switches
- Wastewater Treatment
- Oil & Gas
- LED Lighting
- Schools
- Hospitals

Description

AC surge protector (also known as SPD or lightning protector) 1101-424 from Transtector is a panel style SPD that utilizes state of the art SASD/MOV technology to protect critical equipment that operates on a 120/240 Vac split-phase electrical service. This surge protector provides effective protection against electrical transient surges that are generated both by external lightning events and by internal switching events and supports long-term system reliability by safely shunting high amounts of transient energy while maintaining a very low clamping voltage. Transtector AC surge protectors are available in stock with same day shipping.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Service Voltages		120/240		Vac
Service Type		Split-Phase		
Maximum Continuous Operating Voltage (MCOV)				
L - L			280	Vac
L - N			140	Vac

Surge Protection Specification

Description	Minimum	Typical	Maximum	Units
Surge Protection Technology		SASD, MOV		
Protection Modes		L-N, L-L		
8/20 μ s Surge Current			130	kA
Nominal Discharge Current Rating (In)		10		kA

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:
[AC Surge Protector SPD MCP Panel 120/240 Vac Split-Phase SASD, MOV 130 kA 1101-424](#)

AC Surge Protector SPD MCP Panel 120/240 Vac Split-Phase SASD, MOV 130 kA

1101-424
MCP 120TA-10M OD



Vpl 8/20 μ s L-N	430 @ 3kA	2,080 @ 10kA	Vpk
Response Time		5	ns

Mechanical Specifications

Size		
Height	10.5 in	[266.7 mm]
Width	8.5 in	[215.9 mm]
Depth	6.25 in	[158.75 mm]
Weight	5.8 lbs	[2.63 kg]
Housing Material and Plating	Fiberglass	

Environmental Specifications

Temperature Range (Operational)	-40 to +85 deg C
Environmental Protection Rating	NEMA 4X
Humidity	90% non-condensing

Installation

Mount Type	Panel
Status Indication Terminal	
3-Pin Connector	#16 to #22 AWG

Transtector Systems specializes in protection of highly sensitive, low voltage equipment through its patented, non-degrading silicon diode technology and custom filters. Our power quality expertise translates into a diverse product offering including AC, DC, and signal applications as well as integrated cabinets, power distribution panels and EMP hardened devices.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [AC Surge Protector SPD MCP Panel 120/240 Vac Split-Phase SASD, MOV 130 kA 1101-424](https://www.transtector.com/ac-surge-protector-spd-mcp-panel-120-1101-424-p.aspx)

URL: <https://www.transtector.com/ac-surge-protector-spd-mcp-panel-120-1101-424-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Transtector reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Transtector does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Transtector does not assume any liability arising out of the use of any part or documentation.

1101-424 CAD Drawing

