

AC Surge Protector SPD APEX Panel 240/415 Vac  
3-Phase Wye SASD, MOV 30 kA, UL 94-5V

**1101-494**  
APEX IV X5 240WMR



## Features

- SASD/MOV Hybrid Protection
- Power and Suppression Status LEDs
- Dry Contact Remote Annunciation Wire Leads
- Replaceable Suppression Modules
- NEMA 4X Enclosure

## Applications

- Electrical Panelboards
- Industrial Automation
- Communications Base Stations
- IT & Data Centers
- Switchgear
- Motor Control Centers
- Automatic Transfer Switches
- Wastewater Treatment
- Oil & Gas
- LED Lighting
- Schools
- Hospitals

## Description

AC surge protector (also known as SPD or lightning protector) 1101-494 from Transtector is a UL 94-5V panel style SPD that utilizes state of the art SASD/MOV technology to protect critical equipment that operates on a 240/415 Vac 3-Phase Wye electrical service. This surge protector provides effective protection against electrical transient surges that are generated both by external lightning events and by internal switching events and supports long-term system reliability by safely shunting high amounts of transient energy while maintaining a very low clamping voltage. Transtector AC surge protectors are available in stock with same day shipping.

## Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Service Voltages		240/415		Vac
Service Type		3-Phase Wye		
Maximum Continuous Operating Voltage (MCOV)				
L - L			550	Vac
L - N			275	Vac

## Surge Protection Specification

Description	Minimum	Typical	Maximum	Units
Surge Protection Technology		SASD, MOV		
Protection Modes		L-L, L-N		
8/20 $\mu$ s Surge Current			30	kA

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:  
**AC Surge Protector SPD APEX Panel 240/415 Vac 3-Phase Wye SASD, MOV 30 kA, UL 94-5V 1101-494**

AC Surge Protector SPD APEX Panel 240/415 Vac  
3-Phase Wye SASD, MOV 30 kA, UL 94-5V

**1101-494**  
APEX IV X5 240WMR



Nominal Discharge Current Rating (In)	10	kA
V <sub>pl</sub> 8/20 $\mu$ s L-N	600 @ 500A	V <sub>pk</sub>
Response Time	5	ns
SCCR (Short Circuit Current Rating)	65	kAIC

## Mechanical Specifications

### Size

Height	12.5 in	[317.5 mm]
Width	10.5 in	[266.7 mm]
Depth	6.5 in	[165.1 mm]
Weight	10.5 lbs	[4.76 kg]
Housing Material and Plating	Fiberglass	

## Environmental Specifications

Temperature Range (Operational)	-30 to +65 deg C
Humidity	90% non-condensing

## Installation

Mount Type	Panel
Service Wiring Terminal	
Terminals	#4 to #10 AWG
Status Indication Terminal	
12 Pin Connector	#14 to #22 AWG

## Compliance Certifications

UL Compliant	Yes
Certifications	UL 94-5V

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:  
AC Surge Protector SPD APEX Panel 240/415 Vac 3-Phase Wye SASD, MOV 30 kA, UL 94-5V 1101-494

AC Surge Protector SPD APEX Panel 240/415 Vac  
3-Phase Wye SASD, MOV 30 kA, UL 94-5V

**1101-494**  
**APEX IV X5 240WMR**



Transtector Systems specializes in protection of highly sensitive, low voltage equipment through its patented, non-degrading silicon diode technology and custom filters. Our power quality expertise translates into a diverse product offering including AC, DC, and signal applications as well as integrated cabinets, power distribution panels and EMP hardened devices.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [AC Surge Protector SPD APEX Panel 240/415 Vac 3-Phase Wye SASD, MOV 30 kA, UL 94-5V 1101-494](https://www.transtector.com/ac-surge-protector-spd-apex-panel-240-1101-494-p.aspx)

URL: <https://www.transtector.com/ac-surge-protector-spd-apex-panel-240-1101-494-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Transtector reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Transtector does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Transtector does not assume any liability arising out of the use of any part or documentation.

## 1101-494 CAD Drawing

