

AC Surge Protector SPD APEX Panel 127/220 Vac 3-Phase Wye SASD 10 kA, UL 94-5V

1101-719
APEX IV X5 120 WI



Features

- SASD/MOV Hybrid Protection
- Power and Suppression Status LEDs
- Dry Contact Remote Annunciation Wire Leads
- Replaceable Suppression Modules
- NEMA 4X Enclosure

Applications

- Electrical Panelboards
- Industrial Automation
- Communications Base Stations
- IT & Data Centers
- Switchgear
- Motor Control Centers
- Automatic Transfer Switches
- Wastewater Treatment
- Oil & Gas
- LED Lighting
- Schools
- Hospitals

Description

AC surge protector (also known as SPD or lightning protector) 1101-719 from Transtector is a UL 94-5V panel style SPD that utilizes state of the art SASD technology to protect critical equipment that operates on a 127/220 Vac 3-Phase Wye electrical service. This surge protector provides effective protection against electrical transient surges that are generated both by external lightning events and by internal switching events and supports long-term system reliability by safely shunting high amounts of transient energy while maintaining a very low clamping voltage. Transtector AC surge protectors are available in stock with same day shipping.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Service Voltages		127/220		Vac
Service Type		3-Phase Wye		
Maximum Continuous Operating Voltage (MCOV)				
L - N			170	Vac

Surge Protection Specification

Description	Minimum	Typical	Maximum	Units
Surge Protection Technology		SASD		
Protection Modes		L-L, L-N		
8/20μs Surge Current			10	kA
Nominal Discharge Current Rating (In)		10		kA

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:
[AC Surge Protector SPD APEX Panel 127/220 Vac 3-Phase Wye SASD 10 kA, UL 94-5V 1101-719](#)

AC Surge Protector SPD APEX Panel 127/220 Vac 3-Phase Wye SASD 10 kA, UL 94-5V

1101-719
APEX IV X5 120 WI



Vpl 8/20µs L-N	650 @ 10kA	Vpk
Response Time	5	ns
SCCR (Short Circuit Current Rating)	42	kAIC

Mechanical Specifications

Size

Height	12.5 in	[317.5 mm]
Width	10.5 in	[266.7 mm]
Depth	6.5 in	[165.1 mm]
Weight	8 lbs	[3.63 kg]
Housing Material and Plating	Fiberglass	

Environmental Specifications

Temperature Range (Operational)	-30 to +65 deg C
Humidity	90% non-condensing

Installation

Mount Type	Panel
Service Wiring Terminal Terminals	#4 to #10 AWG
Status Indication Terminal 3-Pin Connector	#14 to #22 AWG

Compliance Certifications

UL Compliant Certifications	Yes UL 94-5V
-----------------------------	-----------------

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:
[AC Surge Protector SPD APEX Panel 127/220 Vac 3-Phase Wye SASD 10 kA, UL 94-5V 1101-719](#)

AC Surge Protector SPD APEX Panel 127/220 Vac
3-Phase Wye SASD 10 kA, UL 94-5V

1101-719
APEX IV X5 120 WI



Transtector Systems specializes in protection of highly sensitive, low voltage equipment through its patented, non-degrading silicon diode technology and custom filters. Our power quality expertise translates into a diverse product offering including AC, DC, and signal applications as well as integrated cabinets, power distribution panels and EMP hardened devices.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [AC Surge Protector SPD APEX Panel 127/220 Vac 3-Phase Wye SASD 10 kA, UL 94-5V 1101-719](#)

URL: <https://www.transtector.com/ac-surge-protector-spd-apex-panel-120-1101-719-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Transtector reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Transtector does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Transtector does not assume any liability arising out of the use of any part or documentation.

4 1101-719 REV 1.1 | © 2019 Transtector, Inc., All Rights Reserved. **+1 208 635 6400** | Transtector.com