

DC Surge Protector SPD DRI Indoor DIN-Rail 24 Vdc,  
Full-Mode SASD Low-Voltage Annunciation

**1101-869**  
DRI 24



## Features

- 100% SASD Protection
- Suppression Status LED
- Dry Contact Remote Annunciation Terminals
- Replaceable Suppression Module
- DIN-Rail Mount

## Applications

- Industrial Automation
- Controls & Sense Loops
- Telecommunications Base Stations
- IT & Data Centers
- Wastewater Treatment
- Rail
- Oil & Gas
- LED Lighting

## Description

DC surge protector (also known as SPD or lightning protector) 1101-869 from Transtector is a DIN-Rail style SPD that utilizes state of the art SASD technology to protect critical equipment that operates on a 24 Vdc electrical service. This surge protector provides effective protection against electrical transient surges that are generated both by external lightning events and by internal switching events and supports long-term system reliability by safely shunting high amounts of transient energy while maintaining a very low clamping voltage. Transtector DC surge protectors are available in stock with same day shipping.

## Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Service Voltages	24			Vdc
Current Rating			5	A
Maximum Continuous Operating Voltage (MCOV)				
MCOV DC			34	Vdc

## Surge Protection Specification

Description	Minimum	Typical	Maximum	Units
Surge Protection Technology		SASD		
Surge Protection Modes		Supply to GND, Supply to Supply		
Response Time			5	ns
VPL 8/20μs L-G			110 @ 1000A	Vpk
VPL 10/1000μs			48 @ 100A	Vpk

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:  
[DC Surge Protector SPD DRI Indoor DIN-Rail 24 Vdc, Full-Mode SASD Low-Voltage Annunciation 1101-869](#)

DC Surge Protector SPD DRI Indoor DIN-Rail 24 Vdc,  
Full-Mode SASD Low-Voltage Annunciation

**1101-869**  
DRI 24



## Mechanical Specifications

### Size

Height	3.36 in	[85.34 mm]
Width	2.06 in	[52.32 mm]
Depth	1.67 in	[42.42 mm]
Weight	0.3 lbs	[136.08 g]
Housing Material and Plating	Nylon	

## Environmental Specifications

### Temperature

Operating Range	-40 to +85 deg C
Storage Range	-40 to +85 deg C
Humidity	99% non-condensing

## Installation

Mount Type	DIN-Rail
Service Wiring Terminal	#28 to #12 AWG
Spring Cage Clamp	#28 to #12 AWG
Status Indication Terminal	#28 to #12 AWG

## Compliance Certifications

Hazardous Locations	Yes
Certifications	Haz Loc AEx/Ex nA nC IIC T4 -40C to +65C
	Class 1 Div 2 Groups A,B,C,D T4A Tamb -40C to +65C
	CE Ex II 3 G Ex nA nC T4 -40C to +65C
	FM10ATEX0002X

Transtector Systems specializes in protection of highly sensitive, low voltage equipment through its patented, non-degrading silicon diode technology and custom filters. Our power quality expertise translates into a diverse product offering including AC, DC, and signal applications as well as integrated cabinets, power distribution panels and EMP hardened devices.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [DC Surge Protector SPD DRI Indoor DIN-Rail 24 Vdc, Full-Mode SASD Low-Voltage Annunciation 1101-869](#)

URL: <https://www.transtector.com/dc-surge-protector-spd-dri-indoor-din-1101-869-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [DC Surge Protector SPD DRI Indoor DIN-Rail 24 Vdc, Full-Mode SASD Low-Voltage Annunciation 1101-869](#)

DC Surge Protector SPD DRI Indoor DIN-Rail 24 Vdc,  
Full-Mode SASD Low-Voltage Annunciation

**1101-869**  
**DRI 24**



---

make modifications to the part and/or the documentation of the part, in order to implement improvements. Transtector reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Transtector does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Transtector does not assume any liability arising out of the use of any part or documentation.

## 1101-869 CAD Drawing

