

## AC Surge Protector SPD CFS Brick 220/380 Vac 3-Phase Wye MOV 120 kA

**A70-00-5012**  
LEA CFS 220/380-3Y



### Features

- High Capacity MOV Protection
- Suppression Status LEDs
- Dry Contact Remote Annunciation Wire Leads

### Applications

- Electrical Panelboards
- Industrial Automation
- Communications Base Stations
- IT & Data Centers
- Switchgear
- Motor Control Centers
- Automatic Transfer Switches
- Wastewater Treatment
- Oil & Gas
- LED Lighting
- Schools
- Hospitals

### Description

AC surge protector (also known as SPD or lightning protector) A70-00-5012 from Transtector is a brick style SPD that utilizes state of the art MOV technology to protect critical equipment that operates on a 220/380 Vac 3-Phase Wye electrical service. This surge protector provides effective protection against electrical transient surges that are generated both by external lightning events and by internal switching events and supports long-term system reliability by safely shunting high amounts of transient energy while maintaining a very low clamping voltage. Transtector AC surge protectors are available in stock with same day shipping.

### Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Service Voltages		220/380		Vac
Service Type		3-Phase Wye		
Maximum Continuous Operating Voltage (MCOV)				
L - L		437		Vac
L - N		253		Vac
L - G		253		Vac
N - G		253		Vac

### Surge Protection Specification

Description	Minimum	Typical	Maximum	Units
Surge Protection Technology		MOV		
Protection Modes		L-N, L-G, N-G, L-L		

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:  
[AC Surge Protector SPD CFS Brick 220/380 Vac 3-Phase Wye MOV 120 kA A70-00-5012](#)

## AC Surge Protector SPD CFS Brick 220/380 Vac 3-Phase Wye MOV 120 kA

**A70-00-5012**  
**LEA CFS 220/380-3Y**



8/20μs Surge Current	120	kA
Response Time	25	ns

### Mechanical Specifications

#### Size

Height	2.4 in	[60.96 mm]
Width	5.29 in	[134.37 mm]
Depth	5.58 in	[141.73 mm]
Weight	5 lbs	[2.27 kg]
Housing Material and Plating	Plastic	

### Environmental Specifications

Temperature Range (Operational)	-40 to +85 deg C
Environmental Protection Rating	NEMA 4X
Humidity	95% non-condensing

### Installation

Mount Type	Panel
------------	-------

Transtector Systems specializes in protection of highly sensitive, low voltage equipment through its patented, non-degrading silicon diode technology and custom filters. Our power quality expertise translates into a diverse product offering including AC, DC, and signal applications as well as integrated cabinets, power distribution panels and EMP hardened devices.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [AC Surge Protector SPD CFS Brick 220/380 Vac 3-Phase Wye MOV 120 kA A70-00-5012](#)

URL: <https://www.transtector.com/ac-surge-protector-spd-cfs-brick-220-a70-00-5012-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Transtector reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Transtector does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Transtector does not assume any liability arising out of the use of any part or documentation.

## A70-00-5012 CAD Drawing

